

Maschinentyp		Arburg 320 C Intern: #3	Ergotech 60/420-200 concept Intern: #2	Ergotech 60/420-200 concept Intern: #9	Ergotech 100/420-430 concept Intern: #6	Ergotech 100/420-430 concept Intern: #7	Arburg 420 C Intern: #10	Ergotech 150/500-610 concept Intern: #8	Arburg 570 C Intern: #5	Mars III 2000/750 Europack Intern: #8	Mars III 3200/1700 Europa pack Intern: #1
Internat. Größenangabe		350-120	600-200	600-200	1000-430	1000-430	420	1500-610	570	2000-750	3200-1700
Schließkraft	KN	350	600	600	1000	1000	1000	1500	2000	2000	3200
Öffnungsweg max.	mm	350	450	450	500	500	500	500	650	490	640
Werkzeugeinbauhöhe min.	mm	200	250	200	250	200	250	250	300	200	250
Werkzeugeinbauhöhe max.	mm	550	700	700	700	700	750	560	950	550	680
Max. Abst. WZ-Aufspannplatte	mm	550	700	750	750	750	750	1060	1170	1040	1320
Werkzeugspannplatte	mm	446x446	600 x 600	600 x 600	600 x 600	600 x 600	490 x 490	750 x 750	815 x 815	790x790	990x990
Säulenabstand	H/V	320x320	420 x 420	420 x 420	420 x 420	420 x 420	420 x 420	500 x 500	570 x 570	530x530	680x680
Werkzeuggewicht max.	kg	400	700	700	700	700	1200	1700	1500		
Schneckendurchmesser	mm	25	30	30	40	40	30	50	50	50	65
Einspritzdruck	bar	2500	1900	1900	2020	2020	2500	1598	2000	1800	1820
Hubvolumen	ccm	59,0	106,0	106,0	231,0	231,0	106,0	399,0	392,0	412,0	929,0
Spritzteilgewicht (PS)	g	54	94	94	205	205	97	360	359	241	404
Kernzug		1	1	1	2	2	2	2	2	2	2
Auswerferlänge max.	mm	125	150	150	150	150	175	160	225	140	160
Zentrierungsdurchmesser	mm	125	125	125	125	125	125	160	125	160	160